

Omega 95

DESCRIPTION:

New formulation Omega 95 is the latest generation of Omega's premier severe saltwater-and corrosive atmosphere-resistant grease. It is characterized by an extremely high load carrying capability, superior resistance to water, unparalleled mechanical stability, enhanced resistance to oxidation and corrosion and exemplary performance in high temperature applications. Omega 95 will continue to lubricate under complete immersion or high water washout applications that no ordinary grease can endure.

ENHANCED CAPABILITIES

New and improved Omega 95 now provides still higher water wash resistance and immersed lubrication performance from its high density characteristics. Not only is improved Omega 95 extremely capable at higher temperatures, it will also perform superbly even at lower temperatures as low as -23°C (or -10°F) or near-arctic conditions !!! Omega 95 also contains absolutely no heavy metals, harmful or environmentally undesirable additives which makes this lubricant suitable for the lubrication of reservoir sluice gates and mechanisms, for freshwater lake and canal equipment, etc.

Due to the enhanced purity performance with this all-new Omega 95 formulation, the traditional applications of lubricating shipboard equipment and dockside equipment -including dry-dock and ship repair/building equipment can be expanded to include steam cleaning equipment used in bottling plants, abattoirs, etc., where wet conditions are combined with high heat and pressurized water wash.

Omega 95 works perfectly in anti-friction bearings, both low and high speed ordinary bearings, for lubricating conveyors and for a large variety of construction, irrigation and agricultural equipment lubrication, where wet conditions are often encountered.

Due to Omega 95's improved stay-put qualities, it will readily withstand the vigorous and often difficult shock loading and high heat encountered in mining where underground water and slush tends to inundate and saturate the equipment. In addition to being the best grease for protection of waterside equipment, Omega 95 now provides its exemplary corrosion resistance to a wider variety of applications.

TYPICAL DATA:

TEST	ASTM TEST METHOD	TEST RESULT
Base Oil		
Viscosity, cSt		
@ 40°C	D-445	221
Flash Point, °C	D-92	249
Pour Point, °C	D-97	-9
Dropping Point, °C	D-2265	318
Worked Penetration,	D-217	
60 strokes		282
Worked 100,000 strokes, % change		2.3
Worked 10,000 strokes, with 50/50 water, % change		8.0
Timken OK Load, Lbs	D-2509	60
Four Ball, EP		
Weld Point, Kg	D-2596	500
Load Wear Index (LWI)	D-2596	65
Four Ball Wear, mm	D-2266	0.39
Rust Prevention Rating	D-1743	1, 1, 1
Water Washout @ 175°F (79.4°C), %	D-1264	1.0
Salt Fog Corrosion, 1 mil d.f.t., hours	B-117	>300
Resistance to Water Spray, % retained	D-4049	80
Wheel Bearing Leakage, gm	D-1263	0.5
Roll Stability, % Change	D-1831	5
Oil Separation, Wt. %	D-1742	0.2
NLGI Grade	---	#2
Operating Temperature Range, °C	---	-23 to 200
Color	----	Tan

MAGNA INDUSTRIAL CO. LIMITED

Total Quality Maintenance

1801, Guardian House, 32 Oi Kwan Road, Wanchai, Hong Kong Tel: (852) 2577 5187 Fax: (852) 2577 3190
E-Mail: magna@magnagroup.com Web Site: www.magnagroup.com

O-95 p.1

MATERIAL SAFETY DATA SHEET

DATE 01 Aug 2014

SECTION 1 - IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

Product Name/Code Omega 95

Company Identification

Omega Manufacturing Division,
Magna Industrial Co. Limited,
1801, Guardian House,
32 Oi Kwan Road,
Wanchai, Hong Kong.

Distributor

Alshawi Trading,
Block 351, Road 51, Bldg 20, Manama - Bahrain.
www.alshawitrading.com
info@alshawitrading.com
P.O.Box 33526

Telephone (852) 25775187
Fax (852) 25773190

Telephone (973) 1755 0019
Fax (973) 1755 5108

SECTION 2 - HAZARDS IDENTIFICATION

Not classified as hazardous.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

<u>Ingredients</u>	<u>CAS Number</u>	<u>Wt.%</u>	<u>Classification</u>
Highly refined mineral oil**	64742-65-0	60-100	-

SECTION 4 - FIRST-AID MEASURES

Eye Contact: Flush with plenty of water for at least 15 minutes. Seek immediate medical attention.

Skin Contact: Wash thoroughly with soap and water. Obtain medical attention in case of skin irritation or other cause for concern.

Inhalation: Move patient to open air.

Ingestion: Do not induce vomiting. Seek immediate medical attention.

MAGNA INDUSTRIAL CO. LIMITED

Total Quality Maintenance

1801, Guardian House, 32 Oi Kwan Road, Wanchai, Hong Kong Tel: (852) 2577 5187 Fax: (852) 2577 3190
E-Mail: magna@magnagroup.com Web Site: www.magnagroup.com

O-95 p.2

SECTION 5 - FIRE-FIGHTING MEASURES

Extinguishing Media: Dry chemical, carbon dioxide. Do not use water.

Special Protective Equipment for Fire Fighters: Self-contained breathing apparatus.

Unusual Fire and Explosion Hazards: Dense smoke. Carbon dioxide, carbon monoxide.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Spillage: Transfer bulk of material into another container. Absorb remaining residue with proper absorbents such as sand, vermiculite. Sweep up and dispose of in accordance with local and national regulations.

SECTION 7 - HANDLING AND STORAGE

Keep containers closed. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Wash clothing before reuse. Keep away from feed and food products.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ACGIH TLV

Highly refined mineral oil 5mg/m³ (oil mist)

Eye Protection: Safety goggles and full-face shield

Hand Protection: Rubber or plastic oil resistant gloves.

Ventilation: Use under well ventilated conditions.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Yellow amber semi-solid grease

Odour: Mineral oil odour

pH: N.A.

MAGNA INDUSTRIAL CO. LIMITED

Total Quality Maintenance

1801, Guardian House, 32 Oi Kwan Road, Wanchai, Hong Kong Tel: (852) 2577 5187 Fax: (852) 2577 3190
E-Mail: magna@magnagroup.com Web Site: www.magnagroup.com

O-95 p.3

Specific Gravity: >1
Vapour Pressure: N.A.
Boiling Point: N.A.
Melting Point: N.A.
Flash Point: Above 190°C
Flammability: N.A.
Evaporation Rate: N.A.
Solubility in Water: Insoluble

SECTION 10 - STABILITY AND REACTIVITY

Stable under normal condition.

Materials to Avoid: Strong oxidizing agents such as hydrogen peroxide, chromic acid, bromine.

Toxic compounds may form on thermal decomposition. Hazardous combustion products: carbon monoxide, carbon dioxide.

SECTION 11 - TOXICOLOGICAL INFORMATION

There is no lethal dose information available.

Inhalation: Inhalation of vapours can cause irritation of the respiratory tract. High concentrations of oils, mists, sprays or vapours can cause chemical pneumonitis.

Skin: May cause irritation, drying and cracking.

Eyes: Cause irritation.

Ingestion: May cause irritation in mouth and stomach, thirst, nausea, vomiting, diarrhoea, with possible collapse if large amounts ingested. Aspiration of material upon vomiting may cause chemical pneumonitis.

SECTION 12 - ECOLOGICAL INFORMATION

No ecological information is available at present.

MAGNA INDUSTRIAL CO. LIMITED

Total Quality Maintenance

1801, Guardian House, 32 Oi Kwan Road, Wanchai, Hong Kong Tel: (852) 2577 5187 Fax: (852) 2577 3190
E-Mail: magna@magnagroup.com Web Site: www.magnagroup.com

O-95 p.4

SECTION 13 - DISPOSAL CONSIDERATIONS

Comply with all local and national regulations regarding disposal.

SECTION 14 - TRANSPORT INFORMATION

UN Number : Not regulated

IATA Class : Not regulated, Packing Group: Not regulated

IMDG Class : Not regulated, Packing Group: Not regulated

Not considered hazardous for transport purpose.

SECTION 15 - REGULATORY INFORMATION

-

SECTION 16 - OTHER INFORMATION

R-phrases: -

S-phrases: -

**The highly refined mineral oil used in this product contains less than 3% DMSO extract as measured by IP 346.

Remarks: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.