

# JCA Counting Scale

## Features

- High resolution in 1/30,000(OIML approved 1/3000)
- Internal resolution 1/600 000
- State-of-art identical design
- Full counting keypad with numeric keys
- Fast display of Weight, Average Piece Weight and Part count
- Special rugged construction and stainless steel weighing pan
- Zero / Tare / Pre-tare / Auto tare / Zero tracking / 50 Preset Unit weight / RTC(time display) / Auto unit weight recomputing
- /Part counting / Sampling / Check weight / Check quantity / Accumulation (50 pieces) / Serial No. /Max. serial No. performance
- Up to 10 types of printing forms
- Option: removable RS-232 interface ×2, relay interface×1 and dual channel (connection to larger platforms and floor scales)
- Achieves a more precise count for small parts, with steady weighing result under any kind of industrial application.



Temperature: -5°C~40°C  
Humidity: 80%



## Specifications

Model	JCA-3K (NON-OIML)	JCA-6K	JCA-15K	JCA-30K	JCA-60K (NON-OIML)
Capacity(kg)	3	6	15	30	60
Division(g)	0.1	0.2	0.5	1	2
Weighing units	g / kg / lb/pcs				
Display	6/5/6digits, 18mm digit height, LCD display with green LED backlight				
Weighing pan(mm)	320×240(stainless steel)				
Dimension(mm)	382×344×124				
Weight	Net weight 7.18kg; Gross weight 7.85kg				
Power supply	AC 110V/220V(AC ± 10%) or rechargeable battery (6V/4A)				
Certification	CE, OIML				

## Sizedraft



**JADEVER**<sup>®</sup>



**Jadever Scale Co., Ltd.**  
Tel : 886-2-22990203  
Fax : 886-2-22990204  
http: www.jadever.com  
E-mail:sales@jadever.com.tw

**Xiamen Jadever Scale Co., Ltd.**  
Tel : 86-592-6037668  
Fax : 86-592-6037028  
http://www.jadever.com  
E-mail:xmjadever@jadever.com.cn

**Jadever Weigtech, Inc.**  
Tel:1-905-482-2618  
Fax:1-905-887-4066  
http://www.jadeverscale.com  
E-mail:james@jadeverscale.com



مؤسسة الشاوي التجارية  
**ALSHAWI TRADING**

**Alshawi Trading**

Block 351, Road 51, Bldg 20, Manama - Bahrain.  
www.alshawitrading.com  
info@alshawitrading.com  
P.O. Box: 33526

Telephone (973) 1755 0019  
Fax (973) 1755 5108