

JL-04(For Floor Scale)

Features

- For floor scale



Specifications

Model	JL-04	Model	JL-04
Rated Capacities(T)	0.25, 0.3, 05, 0.75, 1, 1.5, 2, 2.5, 3, 5, 7.5,10	Temperature range, operating	-30~+70°C
Sensitivity	3.0+0.003mV/V(0.5~10t), 2.0+0.002mV/V(0.25~0.3t)	Maximum safe overload	150 %F.S
Accuracy class	C2~C5	Ultimate Overload	180 %F.S
Zero balance	+1% F.S	Recommend excitation	10-12V DC
TCO	+0.02% F.S/10°C	Maximum excitation	15V DC
TC SPAN	+0.02% F.S/10°C	Protection class	IP67(0.25~0.75t), IP68(1-10t)
Input Impedance	400+10Ω	Construction	Alloy steel; Stainless Steel
Output Impedance	352+3Ω	Cable	3m(0.25-2.5t), 4.2m(3-5t),5m(7.5-10t)
Insulation	≥5000MΩ	Temperature range, compensated	-10°C~+40°C

JADEVER®



Jadever Scale Co., Ltd.
Tel : 886-2-22990203
Fax : 886-2-22990204
http: www.jadever.com
E-mail:sales@jadever.com.tw

Xiamen Jadever Scale Co., Ltd.
Tel : 86-592-6037668
Fax : 86-592-6037028
http://www.jadever.com
E-mail:xmjadever@jadever.com.cn

Jadever Weigtech, Inc.
Tel:1-905-482-2618
Fax:1-905-887-4066
http://www.jadeverscale.com
E-mail:james@jadeverscale.com



مؤسسة الشاوي التجارية
ALSHAWI TRADING

Alshawi Trading

Block 351, Road 51, Bldg 20, Manama - Bahrain.
www.alshawitrading.com
info@alshawitrading.com
P.O. Box: 33526

Telephone (973) 1755 0019
Fax (973) 1755 5108