JL-02 (For Table Scale)

Features

- For bench scale

Specifications

Model	JL-02	Model	JL-02
Rated Capacities(kg)	60,100,150,200, 250,300,350,500	Output Impedance	350±5 Ω
Rated Output	2.0 mV/V±5%	Insulation Impedance	⩾5000 MΩ
Non-linearity	0.02 %F.S	Safe Overload	150 %F.S
Hysteresis	0.02 %F.S	Ultimate Overload	200 %F.S
Repeatability	0.02 %F.S	Operating Temperature Range	-20~60 ℃
Creep(20min)	0.02 %F.S	Recommended Excitation	5~12 VDC
Temperature Effect On Output	0.002 %F.S/℃	Maximum Excitation	15 VDC
Temperature Effect On Zero	0.003 %F.S/℃	Construction	Aluminum Alloy
Zero Balance	±0.0200 mV/V	Protection Class	IP67 / Ip68
Input Impedance	410±15 Ω	Cable	ϕ5×15 cm
Mode of Connection	Red(EXC+),Black(EXC−),Green(SIG+),White(SIG−)		

JADEVER®

Jadever Scale Co., Ltd.
Tel : 886-2-22990203
Fax : 886-2-22990204
http: www.jadever.com
E-mail:sales@jadever.com.tw

Xiamen Jadever Scale Co., Ltd.
Tel : 86-592-6037668
Fax : 86-592-6037028
http://www.jadever.com
E-mail:xmjadever@jadever.com.cn

Jadever Weightech, Inc.
Tel:1-905-482-2618
Fax:1-905-887-4066
http://www.jadeverscale.com
E-mail:james@jadeverscale.com

SHAWI
مؤسسة الشاوي التجارية
ALSHAWI TRADING

Alshawi Trading

Block 351, Road 51, Bldg 20, Manama - Bahrain.
www.alshawitrading.com
info@alshawitrading.com
P.O. Box: 33526

Telephone (973) 1755 0019
Fax (973) 1755 5108