SNUGIII Precision Balance

Features

Temperature：0℃~40℃
Humidity：80%

- High resolution in 1/30000 & 1/60000
- Easy to see bright LCD with green LED backlight
- Wind Shield device for a better weighing result
- Anti-interference for RS / ESD
- Overload and transport devices
- Zero / Tare / Weighing / Piece Count / Sampling / Percentage Weighing/RTC/Check Weighing functions
- Auto shut off for power saving
- Battery symbol on LCD for low battery power indication
- RS -232 as a standard, rear display (optional).
- Ideal for applications including laboratory, jewelry, gold, silver, herbs, quality control, industrial, educational needs or any other use.

Specifications

Model	SNUGIII -150	SNUGIII -300	SNUGIII -600	SNUGIII -1500	SNUGIII -3000
Capacity(g)	150	300	600	1500	3000
Division-1(g)	0.005	0.01/0.005	0.01/0.02	0.05	0.1/0.05
Weighing units	13 weighing units				
Display	6 digits , 14mm digit height, LCD display with green LED back light				
Weighing pan (mm)	Φ125	146×125 (stainless steel)			
Dimension(mm)	220X180X182				
Weight	Net weight 1.15kg; Gross weight 1.85kg				
Power supply	4 C size dry batteries or adaptor				
Certification	CE				

Sizedraft





JADEVER®

Jadever Scale Co., Ltd.
Tel : 886-2-22990203
Fax : 886-2-22990204
http: www.jadever.com
E-mail:sales@jadever.com.tw

Xiamen Jadever Scale Co., Ltd.
Tel : 86-592-6037668
Fax : 86-592-6037028
http://www.jadever.com
E-mail:xmjadever@jadever.com.cn

Jadever Weightech, Inc.
Tel:1-905-482-2618
Fax:1-905-887-4066
http://www.jadeverscale.com
E-mail:james@jadeverscale.com

SHAWI
مؤسسة الشاوي التجارية
ALSHAWI TRADING

Alshawi Trading

Block 351, Road 51, Bldg 20, Manama - Bahrain.
www.alshawitrading.com
info@alshawitrading.com
P.O. Box: 33526

Telephone (973) 1755 0019
Fax (973) 1755 5108