



Super Fluoroether Grease

- *Features super advanced Fluoroether Synthetic formula.*
- *Provides superior resistance to acids and solvents – even radiation.*
- *Offers exceptional oxidative & thermal stability in hostile conditions.*

TRUST	Save Money
OMEGA	Enhance Performance
TO	Extend Service Life

SPECIAL FEATURES

Omega 28 Super Fluoroether Grease is quality engineered for "Mission Impossible - Mission Critical" lubrication applications.

- **Omega 28** features a super advanced Fluoroether Synthetic formula for today's toughest operating environments.
- **Omega 28** is virtually indestructible and provides superior resistance a wide range of acids and solvents – even radiation!
- **Omega 28** offers exceptional oxidation and thermal stability characteristics in even the most hostile conditions. Thermal degradation will generally not occur until direct contact temperatures exceeding 500°F (260°C) are encountered.

OUTSTANDING PROPERTIES

Omega 28 is the super fluoroether synthetic grease that:

- Resists even hydrocarbon fuels while providing exceptional long-lasting lubrication qualities.
- Is compatible with most plastics and elastomeric seal materials.
- Is compatible with most plastics and elastomeric seal materials.
- Stays where applied for outstanding dependability.

Omega 28 is formulated to withstand direct contact with :

- Nitrogen Tetroxide • Unsymmetrical Dimethylhydrazine • Oxygen • Turbine Fuel • Ethyl Alcohol • Boiling Nitric Acid • Boiling Sulfuric Acid • Aniline • Ammonia • Molten Sodium Hydroxide • Hydrazine • Diethylenetriamine • Fluorine • up to 90% Hydrogen Peroxide.

USE FOR

Omega 28 text can be used for a wide range of applications that demand the highest performance lubrication, including:

- Aeronautical Equipment • Drug and Pharmaceuticals Production • Computer Chip and Components Production • Electroplating Plants • Fertilizer Factories • Hospitals and Clinics.

Use **Omega 28** for lubricating pipe threads for high-pressure oxygen pipes and for seals, threads, joints and stems used for liquids, gas and strenuous vacuum service environments.

Omega 28 is also ideal for use on plastics and ceramics.



Omega

The Ultimate Lubricant

ITW PPFK reserves the right to modify or change this product for purposes of improving its performance characteristics.
© 2016 ITW PP & F Korea Limited

The Omega Trade Mark is the property of ITW Inc., and is used under licence by ITW PP & F Korea Limited.



The information contained in this publication is to the best of our knowledge and accurate at the time of issue in October, 2016



The Ultimate Lubricant

28

DESCRIPTION:

Omega 28 is a totally new and exclusive Fluoroether Synthetic Grease that displays exemplary inertness to many chemicals, coupled with exceptional oxidative and thermal stability - even under arduous application environments. It will even resist hydrocarbon fuels and most solvents, while providing exceptional lubrication qualities.

EXEMPLARY STABILITY:

Omega 28 is perfect for virtually any hostile operating environment, including radiation exposure, since the advanced chemistry employed provides this in-novative Omega grease with superior resistance and the ability to withstand the harshest operating conditions including exposure and/or direct contact with:

- Nitrogen Tetroxide
- Oxygen
- Ethyl Alcohol
- Aniline
- Ammonia
- Hydrazine
- Fluorine
- Unsymmetrical Dimethylhydrazine
- Turbine Fuel
- Boiling Sulphuric Acid
- Boiling Nitric Acid
- Molten Sodium Hydroxide
- Diethylenetriamine
- up to 90% Hydrogen Peroxide

It is designed and engineered for critical and previously "impossible" lubricating conditions that conventional greases cannot tolerate, such as lubricating pipe threads for high-pressure oxygen pipes, and for seals, threads, joints and stems used for liquids, gas and strenuous vacuum service environments.

Omega 28 features such highly stable properties that thermal degradation will generally not take place until direct contact temperatures exceeding 500°F (260°C) are encountered. It provides excellent lubrication service for severe applications where chemical resistance and resistance to fuel is required, and where superior film strength needs to be maintained at high temperatures.

WIDE RANGE OF APPLICATIONS:

Omega 28 can be used for a wide range of applications which demand the highest performance lubrication, including aeronautical equipment, satellites, aircraft components, ground support equipment, etc.

Suggested applications include:

- Lubrication of mining, plastic compounding and oil-well drilling equipment.
- Lubrication of O-Rings, plastics & ceramics, couplings, instruments, valves, circuit breakers & railway switch machine bearings.
- Food Processing, Canning & Textile equipment & machinery.
- Lubrication of valves and other fittings used in gaseous, liquid oxygen and reactive chemical processing.
- Anti-Seize applications and as a releasing agent and gasket sealant.

- Lubrication of plug valves, pressure release valves and pumping equipment handling highly reactive or corrosive liquids.
- Lubrication of equipment and instruments used in high vacuum applications, cryogenic apparatus and pneumatic systems.
- Lubrication of bearings used in hot air fans in chemical drying processes and sealed roller bearings of track & chain conveyors in high temperature environments.
- Lubrication of shaft bearings in petrochemical plants that come into contact with aromatic hydrocarbons.
- Lubrication of rolling contact bearings and fan bearings used to cool solid state electronic systems including gyroscopes.
- Lubrication of fuel pump bearings pumping jet fuel.

Omega 28 is also eminently suitable for many critical applications in the Drugs & Pharmaceuticals industry, the manufacture of Computer Chips, in Oxygen Producing plants, Automotive Manufacture (where Painting & Drying Ovens and Conveyors are used), in Electroplating plants, Fertilizer Factories, in Wooden Chipboard Manufactories and as an oxygen pipe sealant in Hospitals, Clinics, Hospices, etc.

TYPICAL DATA:

TEST	ASTM TEST METHOD	TEST RESULT
Base Fluid:-		
Viscosity @ 100°F(37.8°C), cSt	D-445	500
Viscosity @ 210°F(98.9°C), cSt	D-445	43
Viscosity Index	D-2270	144
Flash Point	D-92	None
Pour Point	D-97	-20°F (-28.8°C)
Vapour Pressure	Knudsen Method	
	@ 100°F (37.8°C)	6x10 ⁻⁹ torr
	@ 500°F (260°C)	3x10 ⁻⁴ torr
Evaporation, 5-1/2hours @ 400°F (204°C)	D-972	Less that 1%
Unworked Penetration	D-217	249
Worked Penetration (60Times) @ 77°F (25°C)	D-217	265-295
Oil Separation, 24hrs @ 302°F (150°C)	D-1742	7.5%
Evaporation, 22hrs @ 302°F (150°C)	D-2595	1.1%
Neutralization Number	D-974	0.11mg KOH/g
Specific Gravity @ 25°C (77°F)	---	1.93
Copper Corrosion	D-130	2C, No corrosion
NLGI Grade	---	#2
Operating Temperature Range		-30°C to 260°C (-22°F to 500°F)
Color		Off White

The characteristics given above are typical of current production only and slight batch to batch variations should be expected.

CAUTIONARY NOTE:

Since Omega 28 provides superior lubricity when used as a thread sealant, the use of the torque wrench is recommended when mounting nuts on treated threads to avoid over-tightening. In addition, inhaling vapours from Omega 28 at high temperatures over 480°F (250°C) (such as when smoking) should be avoided.

When applying Omega 28 for the first time, parts to be lubricated should be dismantled and thoroughly purged (cleaned) of any existing greases or oils, using chlorinated solvents in an agitated bath and full soak as Omega 28's chemistry is incompatible with ordinary greases.