



Pin, Bushing & Track Roller Grease

- *Superior ultra-tacky heavy-duty formula ideal for pin, bushing & track roller use.*
- *Super penetration power gets through to the hard-to-lubricate points.*
- *Stays tenaciously in place to give reliable, long-lasting protection.*

TRUST *Save Money*
OMEGA *Enhance Performance*
TO *Extend Service Life*



TW
PERFORMANCE
POLYMERS & FLUIDS®

SPECIAL FEATURES

Omega 64 Pin, Bushing & Track Roller Grease is the "Scientific Answer" to your most difficult pin, bushing and track roller lubrication questions.

- **Omega 64** features a superior ultra-tacky heavy-duty formula that makes it ideal for pin, bushing and track roller applications.
- **Omega 64** has super penetration power to get through to even the most hard-to-lubricate points.
- **Omega 64** stays in place to give dependable long-lasting protection – clings tenaciously to metal and resists squeeze-out.

OUTSTANDING PROPERTIES

Omega 64 is the pin, bushing and track roller grease that:

- Is stringy, tacky and sticky enough to follow the motion of large open bushings – even at slow speeds.
- Forms a seal to keep water away from bearings – special inhibitors protect against oxidation and corrosion.
- Carries up to 10% more oil than ordinary lubricants to ensure wide-spread quality lubrication.
- Flows freely through the small clearance grease passages in track rollers and small pin areas – yet it will not drip.

USE FOR

Omega 64 has been developed to greatly increase the life of your expensive equipment. Use **Omega 64** to lubricate pins, bushings and track rollers. **Omega 64** is also suitable for use in slow-moving industrial gears where a semi-fluid grease is required.



Omega

The Ultimate Lubricant

ITW PPFK reserves the right to modify or change this product for purposes of improving its performance characteristics.
© 2016 ITW PP & F Korea Limited

The Omega Trade Mark is the property of ITW Inc., and is used under licence by ITW PP & F Korea Limited.



The information contained in this publication is to the best of our knowledge and accurate at the time of issue in October, 2016

DESCRIPTION:

Omega 64 is a scientifically-developed, ultra-tacky, heavy-duty and tenacious lubricant. Its aim is the ultimate in lubrication protection for track roller, pin and bushing systems.

OXIDATION RESISTANCE:

Omega 64 has special oxidation inhibitive qualities that resist oxidation. Ordinary greases used for track roller systems easily squeeze out, leaving the vital metal surfaces exposed to oxidation. Oxidation is the forerunner of cancerous corrosion and its resultant downtime.

BUILT TO RESIST CONTAMINATION:

Track roller systems are invariably used in areas where abnormal dust, dirt, grit and similar conditions prevail. Ordinary greases adopted for track roller systems readily absorb dust, dirt and grit. This rapidly forms an abrasive mixture that causes premature wear. Omega 64 however, has built-in 'self healing qualities' that actually form an outer shell after application. This keeps dust, dirt, grit and other contaminants out.

EXTREME PRESSURE:

Omega 64 is loaded with extreme-pressure supplements that resist-

Compression	Impact	Loading
Velocity	Shock	Force
Pressure	Squeeze Out	

RESISTS SQUEEZE-OUT:

Omega 64 stays in position after application. Ordinary greases form large periphery deposits that absorb contaminants and eventually break loose and damage the system. Omega 64 retains its NLGI 00 texture and will not squeeze out. It forms an even, balanced lubricant layer of 'bearings' between frictional faces.

TEMPERATURE-STABLE:

Omega 64 retains its texture at both high and low temperatures. At high temperature, ordinary greases thin out, become liquid and drip off the surfaces intended for lubrication. At cold temperatures, most greases become hard and solidify making lubrication impossible and, during the solidifying process, cause extreme drag and thereby waste energy.

ESPECIALLY BUILT FOR TRACK ROLLER SYSTEMS:

Omega 64 has built-in elasticity that provides the stretchability necessary for track roller system lubrication. It contains lubrimyostic elastomers that form millions of long-strand films. These fine films perform the essential job of stress curve lubrication during track roller link-up chain movement.

TYPICAL DATA:

TEST	ASTM TEST METHOD	TEST RESULT
Mineral Oil Base: -		
Viscosity @100°F, SUS	D-88	3000
Flash point, COC, °C (°F)	D-92	185(365)
Dropping Point, °C (°F)	D-566	Not Applicable
Worked Penetration @25°C	D-217	400-430
Rust Prevention	D-1743	#1 rating
Oxidation Stability, P.S.I. drop in 100 hrs	D-942	5 max.
Water Washout, % loss after 2 hrs. @175°F	D-1264	4
Extreme-Pressure Properties	D-2596	#1 rating
Oil Separation, %	D-1742	Nil
Evaporation loss, % loss, 500 hrs.	IP183/63T	0.07
NLGI Grade	-	#00
Operating Temperature Range, °C (°F)	-	-7 to 149 (20 to 300)
Color	-	Grey

The characteristics given above are typical of current production only and slight batch to batch variations should be expected.