



902

OMEGA 902 Tire Mounting Lubricant



Tire Mounting Lubricant

- *Super savings – saves up to 50% in man-hours over conventional mounting.*
- *Super fitting – provides a superior fit between the tire & rim.*
- *Super protection – contains rust inhibitors to protect the rim against corrosion.*

TRUST OMEGA TO Save Money Enhance Performance Extend Service Life



TW
PERFORMANCE
POLYMERS & FLUIDS®



OMEGA ULTIMATE LUBRICANTS

SPECIAL FEATURES

Omega 902 Tire Mounting Lubricant is designed to assist in all types of tire mounting applications, including large trucks and heavy equipment.

- **Omega 902** saves up to 50% in man-hours over conventional mounting means – saves time and money!
- **Omega 902** provides a superior fit between the tire and rim.
- **Omega 902** contains powerful rust inhibitors to protect rims against corrosion.

OUTSTANDING PROPERTIES

Omega 902 is the tire mounting lubricant that:

- Features specially selected penetrants to protect both natural and synthetic tire rubber compounds.
- Is easy to apply and easy to remove – requires no special preparation and is completely water-soluble so excess can be washed away.
- Contains neither soap nor silicone and is safe to use on all tires, including whitewalls.
- Provides a superior fit between tire and rim to ensure a good grip even in low air pressure applications.
- Is prepared under strict laboratory conditions to ensure consistently high quality.

USE FOR

Omega 902 is specifically formulated to assist in all types of tire mounting applications, including large tractors, trucks and vehicles and heavy equipment of every kind.

Omega 902 is specially recommended for use in high humidity environments where wheel rims easily corrode and make tire mounting especially difficult.



Omega

The Ultimate Lubricant

ITW PPFK reserves the right to modify or change this product for purposes of improving its performance characteristics.
© 2016 ITW PP & F Korea Limited

The Omega Trade Mark is the property of ITW Inc., and is used under licence by ITW PP & F Korea Limited.



The information contained in this publication is to the best of our knowledge and accurate at the time of issue in October, 2016



The Ultimate Lubricant

902

DESCRIPTION:

Omega 902 is designed to assist in all types of tire-mounting applications including large truck and heavy equipment tires.

Omega 902 is an enormous aid in tire-mounting. It saves hours in mounting time and prevents damage to both tire and rim. It provides a superior fit between tire and rim and lubricates the entire wheel, due to the super lubricity and advanced polymer system in Omega 902.

Omega 902 contains neither soap nor silicone and is safe to use on every type of tire including whitewalls.

RUBBER PROTECTION:

With the inclusion of specially-selected penetrates, Omega 902 can actually penetrate both natural and synthetic rubber and, in addition, protect the rim and tire should the need arise for future tire removal. It does not interfere with the adhesion of the tire to the rim.

WATER SOLUBLE:

Omega 902 is easy to handle. It does not require any special solvents. It is made up of special water soluble polymers, potassium, sodium, special additives and synergistic elements all of which will not cause any deterioration to rubber.

RUST PROTECTION:

Omega 902 contains a powerful rust inhibitor which prevents the rim from rusting, thus resulting in longer wheel life. Omega 902 is an absolute must in high humidity environments like snow and damp where wheel rims easily corrode, making tire mounting especially difficult.

QUALITY GUARANTEE:

Omega 902 is manufactured under the strictest laboratory control and is regularly tested to ensure consistently high quality. It is simply the best tire-mounting lubricant available.

TIME SAVER:

Omega 902 can reduce the cost of tire changing by 50% in man-hours alone. It has a super low coefficient of friction which makes it easy to install even heavy-duty and large construction equipment tires.

HOW TO APPLY:

Ready to use: no mixing or dilution required. Merely brush or spray on tire to be mounted. After the tire is mounted, any excess amount of Omega 902 can easily be washed off with water as Omega 902 is completely water soluble.